



SNL SAND

Grading according to IS650 Grade 1 to 3

Source of Sand France

METHOD: CEMENT TESTING

USAGE

The sand is used for mortar cubes.

PHYSICAL AND CHEMICAL CHARACTERISTICS

Standard SNL Sand Grading according to IS650, source of sand France, is a natural and siliceous sand (silica > 98%).

The constituent grains of this natural sand are uncrushed, rounded in shape.

The sand is washed, dried, sieved and prepared in a modern workshop offering all guarantees of quality and regularity.

GRADING AND CONTROLS

Grading is according to standard IS 650 Grade 1 to 3

Tamis (mm)	Passants Cumulés (%)		
	Granulométrie selon IS650 Grade 1 (1 à 2 mm)		
	Valeur moyenne	Valeur minimum	Valeur maximum
2,0	100	100	100
1,6	80		
1,0	0,8	0	1

Tamis (mm)	Passants Cumulés (%)		
	Granulométrie selon IS650 Grade 2 (0,5 à 1 mm)		
	Valeur moyenne	Valeur minimum	Valeur maximum
1,0	100	99	100
0,85	90		
0,5	0,8	0	1

Tamis (mm)	Passants Cumulés (%)		
	Granulométrie selon IS650 Grade 3 (0,50 à 0,09 mm)		
	Valeur moyenne	Valeur minimum	Valeur maximum
0,50	100	99	100
0,20	57		
0,09	<0,5	0	0

The sand is available in Grade 1 to 3 and in Premix equal proportions.

Production controls are carried out by SNL laboratory. A certificate of Analysis is attached to each order.

PACKAGING

SNL Sand Grading according to IS 650 Grade (1 to 3 or Premix) is supplied in 25kg bag.

Deliveries are made individually and on a covered pallet of 2 to 48 bags, protected by a polyethylene cover (road and maritime transport) with reinforced cardboard (maritime transport). The export pallets are with a NIMP15 treatment.

The pallets are not stackable.