



# SNL SAND

## Grading according to BS4550

### Source of Sand France

#### METHOD CEMENT TESTING

#### USAGE

The sand is used for the realization of cement mortar cubes

#### TECHNICAL CHARACTERISTICS CHEMICAL & PHYSICAL

Standard SNL Sand Grading according to BS4550, source of sand France, is a natural and siliceous sand (silica > 98%).

The constituent grains of this natural sand are uncrushed, rounded in shape.

The sand is washed, dried, sieved and prepared in a modern workshop offering all guarantees of quality and regularity.

#### GRADING AND CONTROLS

Grading is according to BS 4550- Part 6. Typical values are:

Sieve (mm) square mesh	Grading Average Values SNL Cumulative Passing (%)	Grading according to BS4550 Cumulative Passing (%)
0,850	100	100
0,800	90	
0,630	10	
0,600	5	0 à 10
0,500	0	
0,400	0	

Production controls are carried out by SNL laboratory. A certificate of Analysis is attached to each order.

#### PACKAGING

SNL Sand Grading according to BS4550-Part 6 is supplied in 25kg bag.

Deliveries are made individually and on a covered pallet of 2 to 48 bags, protected by a polyethylene cover (road and maritime transport) with reinforced cardboard (maritime transport). The export pallets are with a NIMP15 treatment.

The pallets are not stackable.